## crt projectors Why a CRT | CRT Features | Single CRT Specs | 2-Piece CRT Specs Single CRT Specs



	9" CRT Projector	8" CRT Projector	8" CRT Projector
Recommended Screen Size	Width of 80 to 120 inches regardless of format, Minimum 60 inches, Maximum 180 inches.		
Projection Configuration	Front or rear projection. Ceiling or floor mounting. Flat or curved screens.		
Projector to Screen Distance	1.5 x screen wi.	1.3 x screen wi.	1.3 x screen wi.
Image Aspect Ratios	1:1, 4:3, 16:9, 1.85:1, 2.35:1 (adjustable and held in each setup memory)		
Standard Inputs (1 each)	RGBHV Video, Stered	Audio, RS232 Control, Exte	rnal Switcher, Remote
Optional Inputs	Second RGBHV Video, Multi-standard Video Decoder, DVI, SDI		
Outputs	Variable Stereo Audio, RS232 Pass Through		
Video Processors	Compatible with all video scalers.		
HDTV  Computer Displays  Horizontal Scan	Compatible with all RGB output HDTV sources with separate H and V Sync.		
Computer Displays	Will display any standard or non-standard resolution up to 2048 x 1536.		
Horizontal Scan	15 to 152 kHz	15 to 152 kHz	15 to 110 kHz
Vertical Scan rates	38 to 180 Hz		
Video Frequency Response	to 150 Mhz (-3dB)   to 150 Mhz (-3 dB)   to 140 Mhz (-3 dB)		
Resolution	2048 x 1536 at normal brightness and contrast settings		
Peak Brightness	1200 Lumens / 33 FL   1000 Lumens / 28 FL   1000 Lumens / 28 FL		
Vertical Keystone Correction	Up to +/- 15 degrees standard. Optionally higher if required.		
On-Screen Display	Help Screens and Operating / Setup Tutorial (multi-language). Test patterns.		
Projector/Carton Size	29"W x 38"L x 21"H / 38"W x 48"L x 29"H		
Projector/Shipping Weight	210 lbs / 260 lbs   145 lbs / 195 lbs   145 lbs / 195 lbs		
Cabinet Finish	( All models are available in your choice of FerrariTM high-gloss color, including but not limited to red, yellow, silver, black and white. Color samples available. )		
Supplied Accessories	Full-function backlit IR remote control, tool kit, user's manual.		