



PROJECTION TV COOLANT

1915-16SQ – 16 oz squeeze bottle

Introduction

Projection TV heat transfer fluid used by many large screen television manufacturers. Used in projection TV guns.

Features / Benefits

- Heat Transfer Fluid
- Non-Flammable
- Crystal Clear
- For Most Brands of Projection TV's
- Low Odor
- Non-Ozone Depleting



Chemical Components

Component	CAS#
1,2-Ethanediol	107-21-1
1,2,3- Propanetriol	56-81-5

Chemical Properties (MSDS available on request)

- PHYSICAL STATE: Liquid
- ODOR: Faint ethereal odor
- APPEARANCE: Clear, Colorless liquid
- pH: 7
- PERCENT VOLATILE: 65 at 25°C
- VAPOR DENSITY: 2.1 (Air=1)
- BOILING POINT: 197°C (386°F)
- FLASHPOINT AND METHOD: None : ASTM D-56 (Tag C.C.)
- SOLUBILITY IN WATER: Miscible
- DENSITY: 1.15 at 25°C
- (VOC): 748.000 g/L (non-exempt VOC)

Environmental Policy

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Packaging and Availability

Techspray Projection TV Coolant is available in the following size:

1915-16SQ	16 oz. (by vol) squeeze bottle
	12 bottles/case

Resources

Techspray® products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

North America
Techspray
P.O. Box 949
Amarillo, TX 79105
800-858-4043
email: tsales@techspray.com

Europe
ITW Contamination Control
Skejby Nordlandsvej 307
DK-8200 Aarhus N
+45 87 400 220
email: info@itw-cc.com

Countries Outside US
Call to locate a distributor
in your country.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.