

Welcome to the Phoenix Diagnostic ROM

Command Summary

=====

H	- Help	LT	- LED Test
?	- Help	PO	- Power Off
DB	- Display Bytes	LRB	- Byte Loop Read Test
DW	- Display Words	LRW	- Word Loop Read Test
DL	- Display Long Words	LRL	- Long Word Loop Read Test
FB	- Fill Bytes	LWB	- Byte Loop Write Test
FW	- Fill Words	LWW	- Word Loop Write Test
FL	- Fill Long Words	LWL	- Long Word Loop Write Test
MB	- Modify Bytes	RWB	- Byte Ramp Write Test
MW	- Modify Words	RWW	- Word Ramp Write Test
ML	- Modify Long Words	RWL	- Long Ramp Write Test
RAM	- RAM R/W Tests	ROM	- ROM Read Tests
CON	- Conv RAM R/W Tests	SCR	- Chargen RAM R/W Tests
IOT	- IO RAM R/W Tests	VID	- Chargen Waveforms
WAV	- Conv Waveform Tests		
LLI	[control] [16 bit val]		- LLI write access
XH	[0-7]		- Crosshatch Selection
INT	hfreq[Hz] vfreq[Hz*100]		- Internal Freq Test
EXT			- External Freq Test
FLA	- flash memory		

Welcome to the Phoenix Diagnostic ROM ...

=====
=====< AutoDiagnostics Report >=====
=====

- - - Marquee 8500 Control Module Tests - - -

260306 (Mark I board) detected

260336 (Mark II board) detected

WARNING! Unknown control module detected

68000 Register Test :

ROM Checksum : SUMMED = %04x, XOR'ed = %04x

Main RAM R/W Trotting Foxes Test : BYTE %s, WORD %s, LONG %s

Extended RAM R/W Trotting Foxes Test : Trap Vectors (0..15)

That Failed : 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15

Handshaking Test :

DPB RAM R/W Test : VERTICAL %s, HORIZONTAL %s